VERSATILE
RESISTENTE
FUNZIONALE

UN'EVOLUZIONE PER PAVIMENTAZIONI INNOVATIVE. ASSOCIANDO L'INDISCUTIBILE PREGEVOLEZZA ESTETICA DELLE COLLEZIONI PANARIA A PRESTAZIONI TECNICHE DI ALTISSIMO VALORE, NASCE LA VERSIONE DA 20MM DI SPESSORE: LA SOLUZIONE IDEALE PER INFINITE APPLICAZIONI DA ESTERNO.

VERSATILE
RESISTANT
FUNCTIONAL

AN INNOVATIVE EVOLUTION FOR FLOORING. COMBINING AN UNDENIABLE AESTHETICAL PRECIOUSNESS WITH HIGHLY VALUED TECHNICAL PERFORMANCES, HERE IT COMES 20MM OF THICKNESS: PERFECT SOLUT ION FOR COUNTLESS OUTDOOR LIVING AREAS.

CARRABILE
CON POSA SU MASSETTO ADESIVO
SUITABLE
FOR DRIVEWAYS WITH LAYING ON ADHESIVE SCREED

INGELIVO
FROST RESISTANT

RESISTENTE AL SALE
RESISTANT TO SALT

ANTISCIVOLO
R11 A+B+C
ANTISLIP
R11 A+B+C

RESISTENTE AGLI ACIDI
NON RICHIEDE TRATTAMENTI
ACID RESISTANT
NO TREATMENTS NEEDED

RESISTENTE
A SBALZI TERMICI ED AGENTI ATMOSFERICI
RESISTANT
TO THERMAL SHOCKS AND WEATHER CONDITIONS

PRATICO
FACILMENTE POSABILE REMOVIBILE E RIUTILIZZABILE
PRACTICAL
IT CAN BE EASILY LAID, REMOVED AND REUSED

FORTE
RESISTE AI CARICHI DI ROTTURA OLTRE 1000 KG PER LASTRA (60X60 CM)
STRONG
IT RESISTS BREAKING LOADS OVER 1000 KG PER SHEET (60X60 CM)

INATTACCABILE
DA MUFFE E MUSCHIO
NOT AFFECTED
BY MOLD AND MOSS

ETERNO
MATERIA E COLORI STABILI NEL TEMPO
ETERNAL
MATERIAL AND COLOUR STABILITY OVER TIME

RESISTENTE AL FUOCO
FIRE RESISTANT

ECOLOGICO
CREATO NEL RISPETTO E PER LA SALVAGUARDIA DELL'AMBIENTE
ECO FRIENDLY
CREATED TO RESPECT AND SAFEGUARD THE ENVIRONMENT

20mm

APPLICAZIONI
CINQUE SISTEMI DI POSA PER LA MASSIMA VERSATILITÀ DI IMPIEGO IN AMBITO RESIDENZIALE E COMMERCIALE:

APPLICATIONS
FIVE LAYING PATTERNS IDEAL FOR RESIDENTIAL AND COMMERCIAL DESIGNS:

POSA SU MASSETTO CON COLLA
LAYING ON SCREED WITH GLUE

POSA SU GHIAIA O SABBIA
LAYING ON SAND OR GRAVEL

POSA SU ERBA
LAYING ON GRASS

POSA SOPRAELEVATA CON SUPPORTI FISSI
RAISED LAYING WITH FIXED SUPPORTS

POSA SOPRAELEVATA CON SUPPORTI REGOLABILI
RAISED LAYING WITH ADJUSTABLE SUPPORTS

DESTINAZIONI D'USO / INTENDED USE

VIALETTI
WALKWAYS

CAMMINAMENTI PISCINE
POOL DECKS

PARCHEGGI
PARKING AREAS

TERRAZZE
TERRACES

PARCHI PUBBLICI GIARDINI
PUBLIC PARKS GARDENS

STABILIMENTI BALNEARI
BEACH RESORTS

ZONE INDUSTRIALI
INDUSTRIAL AREAS

AREE URBANE
URBAN AREAS

20 mm

PEZZI SPECIALI / TRIM PIECES



1	COSTA TORO ANGOLARE DX 30X60 • 12"X24" RETT. / RECT. COD. ITALIA A90 COD. ESTERO 097	6	COSTA RETTA GRIP 30X60 • 12"X24" RETT. / RECT. COD. ITALIA A79 COD. ESTERO 099
2	COSTA TORO ANGOLARE SX 30X60 • 12"X24" RETT. / RECT. COD. ITALIA A90 COD. ESTERO 097	7	COSTA RETTA ANGOLARE DX 30X60 • 12"X24" RETT. / RECT. COD. ITALIA A77 COD. ESTERO 092
3	COSTA TORO 30X60 • 12"X24" RETT. / RECT. COD. ITALIA A69 COD. ESTERO 090	8	COSTA RETTA ANGOLARE SX 30X60 • 12"X24" RETT. / RECT. COD. ITALIA A77 COD. ESTERO 092
4	COSTA TORO GRIP 30X60 • 12"X24" RETT. / RECT. COD. ITALIA A85 COD. ESTERO 101	9	GRIGLIA 15X60 • 6"X24" RETT. / RECT. COD. ITALIA B07 COD. ESTERO 189
5	COSTA RETTA 30X60 • 12"X24" RETT. / RECT. COD. ITALIA A62 COD. ESTERO 087	10	GRIGLIA ANGOLARE DX 15X60 • 6"X24" RETT. / RECT. COD. ITALIA B11 COD. ESTERO 110
		11	GRIGLIA ANGOLARE SX 15X60 • 6"X24" RETT. / RECT. COD. ITALIA B11 COD. ESTERO 110

DISPONIBILI SU TUTTI I COLORI / ALL COLOURS AVAILABLE

- PREZZO AL PEZZO / PRICE BY PIECE / STÜCKPREIS / PRIX À LA PIÈCE
- VENDUTI SOLO A SCATOLE COMPLETE / VENDUS PAR BOITE COMPLETE / NUR VOLLE KARTON / ONLY FULL BOXES SOLD
- LAVORATI SOLO SU RICHIESTA / SEULEMENT À LA DEMANDE / NUR AUF ANFRAGE / MANUFACTURED ONLY UPON SPECIAL REQUEST
- PER TUTTI I PZ SPECIALI CONSEGNA 30 GG / FOR ALL TRIM PIECES 30 DAYS DELIVERY / LIVRAISON EN 30 JOURS POUR TOUTES LES PIÈCES SPÈCIALES FORMTEILE HABEN 30 TAGE LIEFERZEIT

20mm

I VANTAGGI DELLA POSA SOPRAELEVATA / THE ADVANTAGES OF FLOATING SYSTEM



OTTIMO NASCONDIGLIO PER TUBI ED IMPIANTI

L'intercapedine tra pavimentazione e membrana sottostante, permette il passaggio di tubi ed impianti che vengono così mascherati rimanendo tuttavia facilmente ispezionabili.

EXCELLENT FOR HIDING PIPES AND EQUIPMENT

The void between the paving and membrane can be used to accommodate pipes and services, but retain ease of access.

MIGLIORE ISOLAMENTO TERMICO

L'intercapedine fra pavimentazione e membrana sottostante favorisce un costante passaggio d'aria con maggior durata dell'impermeabilizzazione ed isolamento termico.

BETTER THERTMAL INSULATION

The void between the paving and membrane encourages constant air circulation, extending the life of the waterproofing and improving heat insulation and protecting the surface from UV degradation.

RAPIDO DEFLUSSO DELL'ACQUA

La piccola fuga tra una piastra e l'altra consente il rapido deflusso dell'acqua che viene drenata dalla pendenza sottostante.

QUICK WATER DRAINAGE

The small gap between one slab and another allows water to discharge on to the laying surface and facilitate rapid drainage.

FORTE RESISTENZA AI PESI

La robusta struttura del supporto conferita non solo dall'esperienza nel formulare il compound ma anche dalla filettatura continua tra base e vite, garantisce un prodotto forte, sicuro e duraturo.

HIGH LOADS' RESISTANT

The strong structure of Eterno pedestal, given by its special compound and by the continuous fillet between base and screw, guarantee a strong, safe and long lasting product.

PAVIMENTO SEMPRE PIANO E FACILMENTE ISPEZIONABILE

Il sistema sopraelevato consente di compensare i piccoli dislivelli e le pendenze del piano di posa e di realizzare pavimentazioni perfettamente stabili e piane.
In caso di posa su membrana impermeabilizzante, questa è facilmente accessibile ed ispezionabile in quanto la pavimentazione è semplicemente posata sugli appositi sostegni del sistema.

ALWAYS A FLAT PAVING AND EASILY ACCESSIBLE

With the floating system, you can easily compensate for slight unevenness, irregularities and any gradients on the laying surface creating a perfectly stable and at paved surface. The pedestal design allows for the laying surface and any installed services to be accessed and maintained without damaging the paving.

OTTIMO ASSORBIMENTO DELLE DILATAZIONI

L'indipendenza della pavimentazione e dei supporti di sostegno consente di assorbire le dilatazioni ed i movimenti strutturali.

EXCELLENT ABSORPTION OF STRUCTURAL MOVEMENTS

Being independent, the paving and supports can absorb expansion and structural movements.

SIGNIFICATIVA DIMINUZIONE DEL PESO

Con l'eliminazione del massetto di calcestruzzo, il sistema sopraelevato consente una diminuzione sostanziale del peso che grava sulla struttura ed una reale diminuzione dei costi.

SIGNIFICANT LESS WEIGHT

With no requirement for special surface preparation the, Floating system provides a light weight solution, allowing structures to be built at substantially lower cost.

MIGLIOR ISOLAMENTO ACUSTICO

Grazie alla testa "bi-component" anti scivolamento e anti rumore, il supporto Eterno è l'unico al mondo in grado di abbattere il livello sonoro fino a 25dB.

BETTER ACOUSTIC INSULATION

Thanks to its "bi-component" head, anti-noise and anti-slipping, Eterno pedestal is the only one in the world to provide up to 25dB noise reduction level.

SUPPORTI FISSI / SUPPORT WITH FIXED HEIGHT

DISCHI DI SPESSORE VARIABILE CHE CONSENTONO LA POSA DELLE PIASTRELLE CON UNA SOPRAELEVAZIONE DI: 8, 12, 15 0 20 MM.
DISKS OF VARIABLE THICKNESS ALLOWING THE INSTALLATION OF THE TILES WITH A RAISE OF: 8, 12, 15 OR 20 MM.

1 EH12B/8 8 MM
2 EH12 12 MM
3 EH15 15 MM
4 EH20 20 MM
5 EQUILIBRATORI BASCULANTI BALANCER
6 SPESSORE-LIVELLATORE SHIM LH3 3 MM

SUPPORTI REGOLABILI / ADJUSTABLE PAVING SUPPORTS

STRUTTURA REGOLABILE IN ALTEZZA CON ESCURSIONE COMPRESA TRA 25 E 270 MM. IL SISTEMA DI REGOLAZIONE, INTEGRATO NELLA TESTA DEL SUPPORTO E RAGGIUNGIBILE DALL'ALTRO, PERMETTE UNA COMODA REGOLAZIONE DELL'ALTEZZA SENZA RIMUOVERE LE PIASTRELLE.
A STRUCTURE WITH ADJUSTABLE HEIGHT FROM 25 TO 270 MM. THE ADJUSTABLE DEVICE PRESENT ON THE HEAD OF THE SUPPORT CAN BE EASILY REACHED FROM ABOVE ALLOWING FOR A CORRECT SETTING OF HEIGHT WITHOUT REMOVING THE TILES.



NM1 25 - 40 MM
NM2 40 - 70 MM
NM3 60 - 100 MM
NM4 90 - 160 MM
NM5 150 - 270 MM

SUPPORTI REGOLABILI AUTOLIVELLANTI / SELF LEVELLING ADJUSTABLE SUPPORTS

STRUTTURA COSTITUITA DA UNA BASE IN APPOGGIO ALLA SOLETTA, DA UNA VITE CENTRALE REGOLABILE IN ALTEZZA E DA UNA TESTA AUTOLIVELLANTE IN APPOGGIO AL PANNELLO CON UN SISTEMA DI AUTO REGOLAZIONE DELL'INCLINAZIONE FINO A 5°.
A STRUCTURE CONSISTING OF A BASE FIXED TO THE CONCRETE SUBSTRATE, A CENTRAL SCREW WITH ADJUSTABLE HEIGHT AND A SELF-LEVELLING HEAD FIXED TO THE PANEL WITH A SELF-SETTING SYSTEM UP TO 5°.

SE 1 37,5 - 50 MM
SE 2 50 - 75 MM
SE 3 75 - 50 MM
SE 4 120 - 170 MM
SE 5 170 - 215 MM
SE 6 140 - 230 MM
SE 6 140 - 230 MM
SE 235 - 325 MM
SE 205 - 345 MM
SE 250 - 385 MM
SE 300 - 400 MM
SE 270 - 455 MM
SE 315 - 500 MM
SE 365- 550 MM



CARATTERISTICHE TECNICHE / TECHNICAL FEATURES

GRES A MASSA COLORATA / COLOURED-BODY STONEWARE
ISO 13006-G, EN 14411-G (Bla-UGL), ANSI A137.1 (UNGLAZED PORCELAIN TILE - P1 CLASS)

CARICO DI ROTTURA BREAKING STRENGTH BRUCHLAST CHARGE DE RUPTURE CARGA DE RUPTURA	ISO 10545.4	S ≥ 11.000 N
CLASSE REQUISITI MECCANICI MECHANICAL CLASSIFICATION KLASSE MECHANISCHES ERFORDERNIS RÉSISTANCE MÉCANIQUE CLASIFICACIÓN MECÁNICA	EN 1339-F	U 11
RESISTENZA ALL'ABRASIONE PROFONDA DEEP ABRASION RESISTANCE WIDERSTAND GEGEN TIEFENABRIEB RÉSISTANCE À L'ABRASION PROFONDE RESISTENCIA A LA ABRASIÓN PROFUNDA	ISO 10545.6 ASTM C1243	V ≤ 145 MM^3
DILATAZIONE TERMICA LINEARE LINEAR THERMAL EXPANSION THERMISCHE DILATATION DILATATION THERMIQUE LINÉAIRE DILATACIÓN TÉRMICA LINEAR	ISO 10545.8	α ≤ 7-10 $^{-6}$ °C^{-1}
RESISTENZA AGLI SBALZI TERMICI THERMAL SHOCK RESISTANCE TEMPERATURWECHSELBESTÄNDIGKEIT RÉSISTANCE AUX CHOCS THERMIQUES RESISTENCIA A LOS CAMBIOS DE TEMPERATURA	ISO 10545.9 ASTM C484	RESISTENTE RESISTANT BESTÄNDIG RÉSISTANT RESISTENTE
RESISTENZA ALLA SCIVOLOSITÀ SLIP RESISTANCE RUTSCHFESTIGKEIT RÉSISTANCE AU GLISSEMENT RESISTENCIA DEL RESBALÓN	DIN 51130	R11
	DIN 51097	C (A+B+C)
	BCR-TORTUS	› 0,50
	ASTM C1028	SCOF ≥ 0.60
	ANSI A137.1 BOT 3000	DCOF ≥ 0.65
	PENDULUM AS/NZS AS/NZ S4586:2004	CLASS W
	PENDULUM UNE ENV UNE ENV 12633	CLASS 3
RESISTENZA ALLE MACCHIE STAIN RESISTANCE FLECKENBESTÄNDIGKEIT RÉSISTANCE AUX TACHES RESISTENCIAS A LAS MANCHAS	ISO 10545-14 CTI 81-7 D	5 RESISTENTE RESISTANT BESTÄNDIG RÉSISTANT RESISTENTE
RESISTENZA ALL' ATTACCO CHIMICO CHEMICAL RESISTANCE CHEMISCHE BESTÄNDIGKEIT RÉSISTANCE CHIMIQUE RESISTENCIA A LOS PRODUCTOS QUIMICOS	ISO 10545-13 ASTM C650	ULA, UHA RESISTENTE RESISTANT BESTÄNDIG RÉSISTANT RESISTENTE
RESISTENZA AL GELO FROST RESISTANCE FROSTBESTÄNDIGKEIT RÉSISTANCE AU GEL RESISTENCIA AL HIELO	ISO 10545-12 ASTM C1026	RESISTENTE RESISTANT BESTÄNDIG RÉSISTANT RESISTENTE
REAZIONE AL FUOCO FIRE REACTION FEUERREAKTION RÉACTION AU FEU REACCIÓN AL FUEGO	EN 13823	A1 - A1 FL NESSUNA REAZIONE NO REACTION

IMBALLAGGI E PESI / PACKINGS AND WEIGHTS

FORMATI SIZES	PEZZI SCATOLA PIECES BOX	PESO SCATOLA KG. WEIGHT BOX KG.	MQ. SCATOLA SQM BOX	ML SCATOLA LM BOX	SCATOLE PALLET BOXES PALLET	PESO PALLET KG. WEIGHT PALLET	MQ. PALLET SQM PALLET
60,3X60,3	2	33,5	0,727	-	32	1072	23,27
60X60 RETT. / RECT.	2	32,5	0,720	-	32	1040	23,04
COSTA TORO	1	8,125	0,180	-	100	812,5	18
ANG. COSTA TORO 30X60 RETT. / RECT	1	6,10	0,135	-	100	610	13,50
COSTA TORO GRIP 30X60 RETT. / RECT.	1	8,125	0,180	-	100	812,5	18
COSTA RETTA 30X60 RETT. / RECT.	1	8,125	0,180	-	100	812,5	18
ANG. COSTA RETTA 30X60 RETT. / RECT.	1	6,1	0,135	-	100	610	13,50
COSTA RETTA GRIP 30X60 RETT. / RECT.	1	8,125	0,180	-	100	812,5	18
GRIGLIA 15X60 RETT. / RECT.	1	4	0,09	-	100	400	9
ANG.GRIGLIA 15X60 RETT. / RECT.	1	3,5	0,08	-	100	350	7,87

SUPPORTI CARATTERISTICHE TECNICHE

Il tema dei Pavimenti Sopraelevati ad uso esclusivo per esteri non è ancora soggetto a norme specifiche in ambito europeo. Attualmente l'unica normativa di riferimento è la UNI EN 12825 che non è vincolante ma pone soltanto una serie di parametri prestazionali di riferimento richiesti in ogni prodotto.
Tale norma ha come postulato principale la destinazione di utilizzo dei Pavimenti Sopraelevati nelle finiture interne degli edifici.
È importante sottolineare che i prodotti Buxstone 20 mm soddisfano i requisiti prestazionali previsti dalla norma EN 12825.
Per una maggiore compattezza della pavimentazione, consigliamo l'impiego di n°5 supporti per ciascuna piastrella nel formato 60x60 cm

SUPPORTS TECHNICAL FEATURES

The subject of Raised Flooring exclusively for outdoor use has not yet been standardized at a European level. The only existing reference Standard is UNI EN 12825: this standard by definition is not mandatory but it provides only a series of performance-related reference parameters which are required for each product.
It's important to point out that Buxstone 20 mm products satisfy the performance requirements expected by the Standard EN 12825.
In order to make the paving more compact, we suggest using 5 supports per each 60x60 cm tile.

MANY LAYING SYSTEMS, A UNIQUE END RESULT.

INSTALLATION **ON GRASS**

STEPPING STONE / PAS JAPONAIS

EASY TO LAY
REMOVEABLE
REPOSITIONABLE

INSTALLATION
ON GRASS

The ideal laying solution for creating walkways, barbecue areas and gazebos in the garden: by laying EVO_2/E™ slabs on the ground, you can preserve the underlying lawn, preventing it from being damaged by weights or heavy foot traffic.
The range is also suitable for creating public and residential walkways and outdoor areas.

HOW TO LAY “JAPANESE STEPPING STONES”

To create a path pattern arranging the slabs in the “Japanese stepping stone” style, you need to calculate the number of steps needed to complete the path, then space the slabs at an equal distance along the route. To ensure perfect stability, dig down 5-8 cm (2”-3”), add fine gravel - size 3 to 6 mm (⅛” to ¼”), and compact down before laying the slab. The slabs must not protrude above the lawn level, in order not to damage the lawnmower when cutting the grass.

INSTALLATION ON GRASS



The proposed diagrams and indications are purely indicative of the type of application: please refer to the specific regulations in force in your country in order to lay the floor to the highest technical standards.

For any information and/or suggestion concerning EVO_2/E™ laying systems installation, please refer to the specific manual EVO_2/E™.

INSTALLATION
ON GRAVEL OR SAND



EASY TO LAY
REMOVEABLE
REPOSITIONABLE

INSTALLATION **ON GRAVEL OR SAND**

Laying on gravel ensures correct soil drainage, through the gaps between the slabs, allowing the water to drain off into the ground. This laying solution is ideal for projects where permanent floor laying is not possible.

For installation onto gravel (⅛"-¼") we recommend the use of Mirage spacers as they provide the slabs with support and allow for planar surfaces. The transparency of the material makes them scarcely visible and they can be cut in order to create T-shaped spacers for straightforward installation patterns.

INSTALLATION ON GRAVEL



INSTALLATION ON SAND



The proposed diagrams and indications are purely indicative of the type of application: please refer to the specific regulations in force in your country in order to lay the floor to the highest technical standards.

For any information and/or suggestion concerning EVO_2/E™ laying systems installation, please refer to the specific manual EVO_2/E™.

ADHESIVE INSTALLATION



VEHICULAR FLOORS

ADHESIVE
INSTALLATION

The ideal laying solution for outdoor driveways, car parks, garage ramps, as the laid surface is extremely resistant to both dynamic and concentrated loads. Expansion joints are required, and the gaps between the tiles must be filled with cement-based grout.



The proposed diagrams and indications are purely indicative of the type of application: please refer to the specific regulations in force in your country in order to lay the floor to the highest technical standards.

For any information and/or suggestion concerning EVO_2/E™ laying systems installation, please refer to the specific manual EVO_2/E™.

INSTALLATION ON **RAISED PEDESTAL SYSTEM**

Note: For raised pedestal system please refer to the specific tab - see on page 42.



EASY TO LAY
REMOVEABLE
REPOSITIONABLE
SERVICEABLE

INSTALLATION ON
RAISED PEDESTAL SYSTEM

Installation on raised pedestal system exploits the conventional system of floating or raised floors. With this laying system, all the pipes and wiring systems laid beneath the tiled surface can be inspected at any time. It offers instant accessibility, simply by lifting and removing the slabs.

Installation on raised pedestal system is used mainly on large, regular surfaces, or above previous floors, provided these show no signs of infiltration. The open gaps between the slabs allow the rain water to drain off into the cavity created under the panels. Thus a flat, even floor is obtained, while the underlying waterproof layer will have the gradient required to drain off the rain water.
The load-bearing structure is made of polypropylene feet with a large base and rounded edges, to prevent damage to the insulating layer. This solution allows for any underlying elements to be inspected and offers a practical passage for pipes and wiring.

RAISED PEDESTAL SYSTEM

Note: For raised pedestal system please refer to the specific tab - see on page 42.

The proposed diagrams and indications are purely indicative of the type of application: please refer to the specific regulations in force in your country in order to lay the floor to the highest technical standards.

For any information and/or suggestion concerning EVO_2/E™ laying systems installation, please refer to the specific manual EVO_2/E™.

INSTALLATION ON
RAISED PEDESTAL SYSTEM

FIXED SUPPORT

SUPPORT	TYPE	CODE	HEIGHT (mm)
	EH12	WC50	12
	EH15	WA12	15
	EH20	WC51	20
	LH3	WC52	3

ADJUSTABLE SUPPORT

SUPPORT	TYPE	CODE	HEIGHT (mm)
	NM1	WC22	25-40
	NM2	WA13	40-70
	NM3	WC17	60-100
	LGH2	WV37	2
	LGH3	WF29	3

SELF-LEVELLING SUPPORT

SUPPORT	TYPE	CODE	HEIGHT (mm)
	SE0	WS93	28-38
	SE1	WC18	37,5-50
	SE2	WA14	50-75
	SE3	WC19	75-100
	LGH2	WV37	2
	LGH3	WF29	3

TECHNICAL CHARACTERISTICS OF THE SUPPORTS

SUPPORTS MADE FROM 100% RECYCLABLE MATERIALS	RESISTANT TO ACIDS AND ALKALIS	RESISTANT TO ATMOSPHERIC AGENTS	RESISTANT TO TEMPERATURES FROM -30°C TO +120°C (-90°F TO +250°F)

Note: For raised pedestal system please refer to the specific tab - see on page 42.

NOTE

IF THE APPLICATION OF THE 20 MM SLABS FORESEES THE CERAMIC PRODUCT USED IN STRUCTURAL INSTALLATIONS, THE PROJECT ENGINEER AND/OR CUSTOMER MUST CAREFULLY ASSESS THE PROJECT REQUIREMENTS WITH REGARD TO THE TECHNICAL SPECIFICATIONS OF THE SLABS. TO PREVENT THE RISK OF DAMAGE OR INJURY, THE MANUFACTURER RECOMMENDS:

- WITH REGARD TO A RAISED FLOOR INSTALLATION A CERAMIC SLAB MAY FRACTURE ON IMPACT IF A HEAVY OBJECT FALLS ON IT FROM ANY SIGNIFICANT HEIGHT. THEREFORE THE MANUFACTURER RECOMMENDS TO CHECK THE SPECIFIC INTENDED USE BEFORE STARTING THE INSTALLATION AND TO FOLLOW TABLE FOR RAISED INSTALLATION PROVIDED BELOW. IN CERTAIN CONDITIONS, REINFORCING MUST BE APPLIED ON THE BACK OF THE SLABS (MESH PLUS OR GALVANIZED STEEL SHEET) SUPPLIED AND APPLIED BY THE MANUFACTURER;
- WITH REFERENCE TO ANY DRY INSTALLATION SYSTEM OF FLOORING ABOVE THE GROUND LEVEL, THE MANUFACTURER RECOMMENDS TO COMPLY WITH LOCAL REGULATIONS AND CONDITIONS OF USE WITH REGARD TO WIND-LOAD, LOADBEARING, SEISMIC EVENTS, ETC.

FAILURE TO COMPLY WITH THESE RECOMMENDATIONS MAY LEAD TO IMPROPER USE OF THE PRODUCT AND COULD CAUSE SERIOUS DAMAGE OR INJURY.

INSTALLATION ON
RAISED PEDESTAL SYSTEM

size	up to 2 cm (3/4")	above 2 cm (3/4")
60x60 cm / 24"x24" (rated) 4 supports per slab	4 SUPPORTS (0,32 pcs/sq ft)	Please contact Mirage®
45x90 cm / 18"x36" (rated) 60x120 cm / 24"x48" (rated) 6 supports per slab	6 SUPPORTS (0,32 pcs/sq ft 60x120 cm / 24"x48") (0,56 pcs/sq ft 45x90 cm / 18"x36")	
30x120 cm / 12"x48" (rated) 6 supports per slab	6 SUPPORTS (0,65 pcs/sq ft)	
20x120 cm / 8"x48" (rated) 6 supports per slab	WITH SPECIAL STRUCTURE, SEE E_DECK CATALOGUE	
90x90 cm / 36"x36" (rated) 4 supports per slab	4 SUPPORTS (0,28 pcs/sq ft)	

Note: For any detail and technical specification concerning the fiber mesh plus or the galvanized steel sheet, please contact Mirage®. Mirage® is responsible only if it supplies the whole system (tile + fiber mesh plus or galvanized sheet). Mirage® cannot be held responsible for reinforcing systems that has not supplied. In case of breakage, tile must be replaced immediately.

FIBER MESH *PLUS*

GALVANIZED STEEL SHEET

To ensure drainage of the tread surface, appropriate transversal or longitudinal gradients should be included during levelling and compaction.
Please remember in any case that, in view of the distinctive advantages of porcelain stoneware, EVO_2/E™ absorbs practically no water, which makes it highly frost-proof. This may lead to localised water pooling, mainly on the edges of the tiles, independently of the manner and quality of the laying. Laying is also recommended with a minimum gap of 3 mm (1/8").