



DOMO

TECHNICAL DATA SHEET

SIZES: 8" x 48", 24" x 48", 24" x 24", 36" x 36", 12" x 24"

FINISHES: MATTE/TEXTURED

PRODUCT: PORCELAIN

EN 14411: 2012 Annex G Group Bla GL

TEST DESCRIPTION	TEST METHOD	TEST VALUE
Dimensions + Surface quality	ISO 10545-2	Complies with Standard
Water Absorption	ISO 10545-3	0.04 %
Average Bending Strength	ISO 10545-4	43.2 N/mm ²
Breaking Strength	ISO 10545-4	21300 N
Resistance to Surface Abrasion	ISO 10545-7	CLASS 4
Crazing resistance	ISO 10545-11	Resistente / Resistant
Frost resistance	ISO 10545-12	Resistente / Resistant
Stain Resistance	ISO 10545-14	CLASS 5
Chemical Resistance (Domestic use and swimming pool chemicals)	ISO 10545-13	CLASS A
Coefficient of Friction	B.C.R.A METHOD	DRY: > 0.04 WET: > 0.04
Antislip Properties	DIN 51130	MATTE: R10 OUTDOOR: R11
Antislip Properties on Wet Surfaces	DIN 51097	OUTDOOR: A+B
Dynamic Coefficient of Friction	DCOF	MATTE: WET: > 0.42 OUTDOOR: WET: > 0.55
Slip Potential	STANDARDS BS 7976-2:2002	MATTE: DRY: 54 WET: 37
Recycled Content	ALL COLORS	40% Pre-consumer