



STORY

TECHNICAL DATA SHEET

SIZES: 30" x 60", 12" x 24", 24" x 48", 24" x 24", 36" x 36", 48" x 48"

FINISHES: MATTE

MOSAICS: Hexagon 9"x13" + Square 12"x12" (2"x2" dot)

PRODUCT: GL PORCELAIN

TEST DESCRIPTION	TEST METHOD	TEST VALUE
Dimensions + Surface quality	UNE EN ISO 10545-2	Complies with the standard
Water Absorption	UNE EN ISO 10545-3	$E \leq 0.5$
Average Bending Strength	UNE EN ISO 10545-4	≥ 35 N/mm ²
Breaking Strength	UNE EN ISO 10545-4	> 1300 N
Thermal Shock Resistance	UNE EN ISO 10545-9	Complies with the standard
Crazing resistance	UNE EN ISO 10545-11	Complies with the standard
Frost resistance	UNE EN ISO 10545-12	Complies with the standard
Stain Resistance	UNE EN ISO 10545-14	Complies with the standard
Chemical Resistance (Domestic use and swimming pool chemicals)	UNE EN ISO 10545-13	CLASS A Minimum HB Minimum LB
Coefficient of Friction	DCOF AcuTest ANSI Standard	Anti-slip Dcof (>0.42)
Antislip Properties	DIN 51130 UNE 41901 EX	Anti-slip R.11 Anti-slip Class 1
Antislip Properties on Wet Surfaces	DIN 51097	Anti-slip Class B
Scratch Hardness	UNE EN 67-101-92	6

CE MARKING: 004CPR-PR/11-4-2013