

# Carlton Sand 2CM



## SIZES

24" x 36"  
24" x 24"

All sizes are nominal and in inches. Special cut sizes and additional trim pieces are available upon meeting a required minimum order quantity.

## LEAD TIME

**1-5 Business Days** | All sizes and finishes

Lead times are approximate and can vary based on quantity ordered, production schedule & delivery location.

## TRIMS

All available trim pieces can be found in the technical data sheet - Please see download below.

## FORMAT + THICKNESS

Paver | 3/4"

Most of our tiles are rectified and micro-beveled, however we recommend confirming with us prior should this be a necessity.

## FINISHES

Textured

All pavers contain a special anti-slip finish and pass all wet condition requirements.

---

## APPLICATIONS

Exterior  
Heavy Traffic  
Walls

Floors  
Interiors  
Wet

Our pavers are suited for all high-traffic outdoor applications and exceed all of the technical requirements from frost and heat resistance, to stain and chemical abrasion. They even have an absurdly high breaking strength and low water absorption rate all to keep your pavers looking brand new for generations.

---

## TECHNICAL DATA

Our pavers can be installed through 3 different methods: Pedestals, Traditional Adhesive, or directly onto soil, grass, and gravel.

Please refer to the Technical Data Sheet for the complete technical details.

---

## CARE + MAINTENANCE

Please refer to our Stone + Tile 101 page for a complete guide

[www.nascostonetile.com/stone-tile-101](http://www.nascostonetile.com/stone-tile-101)