


# Agglo Alpi



## SIZES

- |                                    |                                       |
|------------------------------------|---------------------------------------|
| <input type="checkbox"/> 12" x 24" | <input type="checkbox"/> 12" x 12"    |
| <input type="checkbox"/> 16" x 16" | <input type="checkbox"/> 18" x 18"    |
| <input type="checkbox"/> 24" x 48" | <input type="checkbox"/> 24" x 24"    |
| <input type="checkbox"/> 48" x 48" | <input type="checkbox"/> Slabs 1.2 CM |
| <input type="checkbox"/> Slabs 2CM | <input type="checkbox"/> Slabs 3CM    |

Sizes listed are recommended, any and all sizes are available upon request.

All sizes are nominal and in inches. Special cut sizes and additional trim pieces are available upon meeting a required minimum order quantity.

Slabs available in 120" x 49".

\*Custom colors and aggregate sizes are available upon request with a minimum order quantity of 10,000 SF\*

## LEAD TIME

### 6-8 Weeks

Lead times are approximate and can vary based on quantity ordered, production schedule & delivery location. Slab Disclaimer: this color in SLAB format is special order with a quantity requirement of 2 slabs minimum in order to safely pack and secure the slabs during the shipping journey. There is NO minimum for any tile sizes. Need less than 2 slabs? Please provide us with exact dimensions of what's needed. We can custom cut the slab to size in order to fit the material in a secure crate and avoid any breakage while shipping. For any further clarification or questions, please feel free to contact us directly.



---

## TRIMS

All available bases and coping are available in any size and thickness upon request.

---

## FORMAT + THICKNESS

Slab | 1/2 - 3/4 - 1.25

Tile | 1/2 - 3/4 - 1.25

Thickness is determined by product size and format. Sizes larger than 24x48 typically require a minimum thickness of 3/4".

1/2" Thick Slabs are only recommended for wall applications.

Most of our tiles are rectified and micro-beveled, however we recommend confirming with us prior should this be a necessity.

---

## FINISHES

- ☐ Brushed
- ☐ Honed
- ☐ Polished

---

## APPLICATIONS

Floors  
Interiors  
Wet

Heavy Traffic  
Walls

"Wet" application only applies to honed or textured finishes.

---

## TECHNICAL DATA

Honed finish passes required DCOF Rating of .42

Agglo is comprised of 97% Marble and 3% Resin.

Please refer to the Technical Data Sheet for the complete technical details.

---

## CARE + MAINTAINCE

Please refer to our Stone + Tile 101 page for a complete guide  
[nasco.com/stone-tile-101](https://www.nasco.com/stone-tile-101)

Request Quote | Sample



MORE FROM  
**AGGLO**  
COLLECTION

