


Agglo Black Royal

Request Quote | Sample



SIZES

- | | |
|------------------------------------|---------------------------------------|
| <input type="checkbox"/> 12" x 24" | <input type="checkbox"/> 12" x 12" |
| <input type="checkbox"/> 16" x 16" | <input type="checkbox"/> 18" x 18" |
| <input type="checkbox"/> 24" x 48" | <input type="checkbox"/> 24" x 24" |
| <input type="checkbox"/> 48" x 48" | <input type="checkbox"/> Slabs 1.2 CM |
| <input type="checkbox"/> Slabs 2CM | <input type="checkbox"/> Slabs 3CM |

Sizes listed are recommended, any and all sizes are available upon request.

All sizes are nominal and in inches. Special cut sizes and additional trim pieces are available upon meeting a required minimum order quantity.

Slabs available in 120" x 49".

Custom colors and aggregate sizes are available upon request with a minimum order quantity of 10,000 SF

LEAD TIME

6-8 Weeks | All sizes.

Lead times are approximate and can vary based on quantity ordered, production schedule & delivery location. Slab Disclaimer: this color in SLAB format is special order with a quantity requirement of 2 slabs minimum in order to safely pack and secure the slabs during the shipping journey. There is NO minimum for any tile sizes. Need less than 2 slabs?

Please provide us with exact dimensions of what's needed. We can custom cut the slab to size in order to fit the material in a secure crate and avoid any breakage while shipping. For any further clarification or questions, please feel free to contact us directly.



TRIMS

All available bases and coping are available in any size and thickness upon request.

FORMAT + THICKNESS

Slab | 1/2 - 3/4 - 1.25

Tile | 1/2 - 3/4 - 1.25

Thickness is determined by product size and format. Sizes larger than 24x48 typically require a minimum thickness of 3/4".

1/2" Thick Slabs are only recommended for wall applications.

Most of our tiles are rectified and micro-beveled, however we recommend confirming with us prior should this be a necessity.

FINISHES

- ☐ Brushed
- ☐ Honed
- ☐ Polished

APPLICATIONS

Floors
Interiors
Wet

Heavy Traffic
Walls

"Wet" application only applies to honed or textured finishes.

TECHNICAL DATA

Honed finish passes required DCOF Rating of .42

Agglo is comprised of 97% Marble and 3% Resin.

Please refer to the Technical Data Sheet for the complete technical details.

CARE + MAINTAINCE

Please refer to our Stone + Tile 101 page for a complete guide
[nasco.com/stone-tile-101](https://www.nasco.com/stone-tile-101)

Request Quote | Sample





MORE FROM
AGGLO
COLLECTION

