

# Solstice



## SIZES

12" x 24"	18" x 18"
2 CM	24" x 24"
24" x 48"	3 CM
3" x 6"	32" x 32"
4" x 16"	48" x 48"
6" x 24"	

Sizes listed are recommended, any and all sizes are available upon request without any minimums.

## LEAD TIME

**9-11 Weeks** | All Sizes + Finishes

Lead times are approximate and can vary based on quantity ordered, production schedule & delivery location. **Slab Disclaimer:** this color in SLAB format is special order with a quantity requirement of 12 slabs minimum in order to safely pack and secure the slabs during the shipping journey. There is NO minimum for any tile sizes. **Need less than 12 slabs?** Please provide us with exact dimensions of what's needed. We can custom cut the slab to size in order to fit the material in a secure crate and avoid any breakage while shipping. For any further clarification or questions, please feel free to contact us directly.

## TRIMS

All available trims such as coping, bases, saddles, moldings, and treads are available in any size, edge detail, and thickness upon request.

## FORMAT + THICKNESS

Paver | 3/4"  $\hat{=}$  1.25"  $\hat{=}$  2"  $\hat{=}$  3"  
Slab | 3/4"  $\hat{=}$  1.25"  $\hat{=}$  2"  $\hat{=}$  3"  
Tile | 3/8"  $\hat{=}$  1/2"

Thickness is determined by product size, application, and format.

---

## FINISHES

Brushed  
Flamed  
Polished

Bush-Hammered  
Honed

---

## APPLICATIONS

Exterior  
Floors  
Interiors  
Wet

Facade  
Heavy Traffic  
Walls

“Wet” application only applies to honed or textured finishes.

---

## TECHNICAL DATA

Honed finish passes required DCOF  
Rating of .42

Granite is an extremely dense material and therefore inherently extremely durable making it one of the few natural stones suitable for high-traffic commercial and exterior spaces.

Please refer to the Technical Data Sheet for the complete technical details.

---

## CARE + MAINTAINCE

Please refer to our Stone + Tile 101 page for a complete guide

[nasco.com/stone-tile-101](https://www.nasco.com/stone-tile-101)