



Supreme Black



SIZES

- | | |
|------------------------------------|------------------------------------|
| <input type="checkbox"/> 12" x 24" | <input type="checkbox"/> 18" x 18" |
| <input type="checkbox"/> 2 CM | <input type="checkbox"/> 24" x 48" |
| <input type="checkbox"/> 24" x 24" | <input type="checkbox"/> 3 CM |
| <input type="checkbox"/> 3" x 6" | <input type="checkbox"/> 32" x 32" |
| <input type="checkbox"/> 4" x 16" | <input type="checkbox"/> 48" x 48" |
| <input type="checkbox"/> 6" x 24" | |

Sizes listed are recommended, any and all sizes are available upon request without any minimums.

LEAD TIME

1-5 Business Days | 12" x 12" Polished + Honed 12" x

24" Polished 18" x 18" Polished + Honed + Flamed

24" x 24" Polished + Honed **9-11 Weeks** | All Other

Sizes + Finishes

Lead times are approximate and can vary based on quantity ordered, production schedule & delivery location. Slab Disclaimer: this color in SLAB format is special order with a quantity requirement of 12 slabs minimum in order to safely pack and secure the slabs during the shipping journey. There is NO minimum for any tile sizes. Need less than 12 slabs?

Please provide us with exact dimensions of what's needed. We can custom cut the slab to size in order to fit the material in a secure crate and avoid any breakage while shipping. For any further clarification or questions, please feel free to contact us directly.

TRIMS

All available trims such as coping, bases, saddles, moldings, and treads are available in any size, edge detail, and thickness upon request.

FORMAT + THICKNESS

Paver | 3/4" • 1.25" • 2" • 3"

Slab | 3/4" • 1.25" • 2" • 3"

Tile | 3/8" • 1/2"

Thickness is determined by product size, application, and format.

FINISHES

☐ Brushed

☐ Flamed

☐ Polished

☐ Bush-Hammered

☐ Honed

APPLICATIONS

Exterior

Floors

Interiors

Wet

Facade

Heavy Traffic

Walls

"Wet" application only applies to honed or textured finishes.

TECHNICAL DATA

Honed finish passes required DCOF Rating of .42

Granite is an extremely dense material and therefore inherently extremely durable making it one of the few natural stones suitable for high-traffic commercial and exterior spaces.

Please refer to the Technical Data Sheet for the complete technical details.

CARE + MAINTAINCE

Please refer to our Stone + Tile 101 page for a complete guide

[nasco.com/stone-tile-101](https://www.nasco.com/stone-tile-101)

GRANITE
PAVER
MORE FROM
COLLECTION

