

Calacatta Rose



SIZES

- | | |
|------------------------------------|---|
| <input type="checkbox"/> 12" x 24" | <input type="checkbox"/> 12" x 12" |
| <input type="checkbox"/> 18" x 36" | <input type="checkbox"/> 18" x 18" |
| <input type="checkbox"/> 2 CM | <input type="checkbox"/> 24" x 48" |
| <input type="checkbox"/> 24" x 24" | <input type="checkbox"/> 3 CM |
| <input type="checkbox"/> 3" x 6" | <input type="checkbox"/> 3.25" x 15.75" |
| | Chevron |
| <input type="checkbox"/> 36" x 36" | <input type="checkbox"/> 4" x 12" |
| <input type="checkbox"/> 48" x 48" | <input type="checkbox"/> 6" x 6" |
| <input type="checkbox"/> 6" x 12" | <input type="checkbox"/> Mosaic |
- Sizes listed are recommended, any and all tile sizes are available upon request.

All sizes have a minimum order quantity of 300 SF.

LEAD TIME

1-5 Business Days | 12"x 24" Honed

6-8 Weeks | All Other Sizes + Finishes

Lead times are approximate and can vary based on quantity ordered, production schedule & delivery location. Slab Disclaimer: this color in SLAB format is special order with a quantity requirement of 12 slabs minimum in order to safely pack and secure the slabs during the shipping journey. There is NO minimum for any tile sizes. Need less than 12 slabs? Please provide us with exact dimensions of what's needed. We can custom cut the slab to size in order to fit the material in a secure crate and avoid any breakage while shipping. For any further clarification or questions, please feel free to contact us directly.



TRIMS

All available trims such as bases, saddles, moldings, and treads are available in any size, edge detail, and thickness upon request.

FORMAT + THICKNESS

Slab | 3/4" • 1.25"

Tile | 3/8" • 5/8" • 1/2" • 3/4"

Thickness is determined by product size, application, and format.

Most of our tiles are rectified and micro-beveled, however we recommend confirming with us prior should this be a necessity.

FINISHES

- ☐ Honed
 - ☐ Polished
-

APPLICATIONS

Floors	Interiors
Walls	Wet

"Wet" application only applies to honed finish.

TECHNICAL DATA

Honed finish passes required DCOF Rating of .42

Marble is a naturally occurring material sourced from mother nature herself. A range of character and color variation is to be expected and is a part of its inherent beauty. Nasco is well-known for its hands on approach during the sourcing process to properly control this range and variation so that the material not only maintains design integrity but also its inherent natural beauty. Images are intended to be used as a general guide.

CARE + MAINTAINCE

All marble should be properly set, sealed, and maintained.

Please refer to our Stone + Tile 101 page for a complete guide
nasco.com/stone-tile-101

Request Quote | Sample



MORE FROM
TILE
COLLECTION

