

# G-Stone

COLOR BODY PORCELAIN

MADE WITH HIGH DEFINITION GRAPHICS

SIZE	BEIGE	NERO	HAZELNUT	NUTMEG	SILVER	GRIGIO	UNIT OF MEASURE
<b>MODULAR FIELD TILE</b>							
12 x 12	1095533	1095532	1095529	1095531	1095534	1095530	SF
18 x 18	1095584	1095583	1095580	1095582	1095585	1095581	SF
6 x 24	1095562	1095561	1095558	1095560	1095563	1095559	SF
12 x 24	1095568	1095567	1095564	1095566	1095569	1095565	SF
11.54 x 23.19 Semi-Polished / Rectified*	1095539	1095538	1095535	1095537	1095540	1095536	SF
18 x 36 Rectified*	1095578	1095577	1095574	1095576	1095579	1095575	SF
<b>TRIMS &amp; MOSAICS</b>							
Cove Base 6 x 12	1095527	1095526	1095523	1095525	1095528	1095524	PC
Inside Corner 1 x 6	1095521	1095520	1095517	1095519	1095522	1095518	PC
Outside Corner 1 x 6	1095515	1095514	1095511	1095513	1095516	1095512	PC
Bullnose 3 x 12	1095590	1095589	1095586	1095588	1095591	1095587	PC
Mosaic 2 x 2	1095596	1095595	1095592	1095594	1095597	1095593	PC

SIZE	SF / CTN	PIECES / CTN	CTN / PALLET	UM / PALLET	WEIGHT (lbs) / CTN	WEIGHT (lbs) / PALLET
<b>PACKAGING SPECIFICATIONS</b>						
12 x 12	14	14	48	672	57.4	2755
18 x 18	15.75	7	32	504	64.5	2116
6 x 24	14	14	48	672	57.4	2805
12 x 24	14	7	48	672	57.4	2805
11.54 x 23.19 Semi-Polished / Rectified*	13.02	7	48	624.96	53.38	2562
18 x 36 Rectified*	13.5	3	27	364.5	59.4	1654
Cove Base 6 x 12	NA	10	NA	480	17.5	NA
Inside Corner 1 x 6	NA	4	NA	NA	1	NA
Outside Corner 1 x 6	NA	4	NA	NA	1	NA
Bullnose 3 x 12	3	12	168	504	12.7	2183.6
Mosaic 2 x 2	10	10	45	450	40.6	1877

**MARKETING & MERCHANDISING MATERIALS:**

Please call your Customer Service Representative

**TECHNICAL SPECIFICATIONS**

		Natural	Semi-Polished	
Thickness:		9 mm		
Thickness: 18 x 36 Rectified*		10 mm		
Thickness: Cove Base & Corners		8 mm		
Shade Variation		V2		
Surface Abrasion	PEI	IV		ASTM C1027
Water Absorption		≤ 0.5 %		ASTM C373
Chemical Resistance		NOT AFFECTED		ASTM 650
Dynamic Coefficient of Friction DCOF		≥ 0.50		ANSI 137.1
Stain Resistance		NOT AFFECTED		ASTMC1378
Breaking Strength	9mm	≥ 400		ASTM C648
	8mm	≥ 300		ASTM C648
Resistance to Freeze		RESISTANT		ASTM C1026
Scratch Hardness		≥ 7		MOHS