

MARBLES / Marbles



Porcelain



Floor Tiles



Wall Tiles



Polished finish






Glossy Finish



Strong Variation

Espesor (mm)
Thickness

   	11,5	60 x 120 ^R Nawan
	11,5	60 x 60 ^R Nawan
  	9,3	29,5 x 90 ^R
















CARACTERÍSTICAS TÉCNICAS Technical features

ISO 13006

UNE-EN 14411

NAWAN

	Longitud y anchura Length and width	± 0,6 %	± 0,2 %
	Espesor Thickness	± 5,0 %	± 2,0 %
	Rectitud de lados Straightness of sides	± 0,5 %	± 0,2 %
	Ortogonalidad Rectangularity	± 0,5 %	± 0,2 %
	Planitud de superficie Surface flatness	± 0,5 %	± 0,2 %
	Apariencia superficial Surface appearance	± 95 %	Cumple Norma Complies with standard
	Absorción de agua Water absorption	$E \leq 0,5 \%$	$E \leq 0,5 \%$
	Fuerza de rotura (N) Breaking strength	> 1300 N	> 2500 N
	Resistencia a la flexión (N/mm ²) Modulos of rupture	> 35 N/mm ²	> 45 N/mm ²
	Coefficiente de dilatación térmica lineal (1/k) Coefficient of linear thermal expansion	Valor declarado Declared value	$6,7 \times 10^{-6}$
	Resistencia al choque térmico Thermal shock resistance	Exigida Required	Resiste Resists
	Resistencia al cuarteo Crazing resistance	Exigida Required	Resiste Resists
	Resistencia a la helada Frost resistance	Exigida Required	Resiste Resists

*Características técnicas de los formatos 60 x 60^R / 60 x 120^R

Only technical features of 60 x 60^R / 60 x 120^R